

RU 40

- Snaga magneta 20.000 N
- Namještanje pogonske jedinice po visini zbog dvostruke vodilice (lastin rep).
- Dugme za lijevi/desni smjer okretaja
- 4-brzinski mjenjač
- Rezne brzine
- Jak motor
- Serijsko fino podešavanje prigušeno
Pomično polje: +/-10,0 mm
Okretno polje: +/- 30°



Br. proizvoda: 108 040 RU

Tehnički podatci:



Snaga magneta:
20.000 N



Težina:
22,0 kg



Urezivanje navoja:
M 3 - M 30



Snaga motora:
1.800 W



Pričvršćivanje:
Morze konus MK 3



Dubina bušenja svrdla za jezgre:
do 110,0 mm



Okretaji:
50 - 110 | 75 - 175 okr/min.
105 - 245 | 165 - 385 okr/min.



Stezna glava:
1,0 - 16,0 mm



Napon:
220 - 240 Volt



Visina:
642,0 - 702,0 mm



Krunsko svrdlo:
Ø 12,0 - 80,0 mm



Kompatibilnost:
VDE, CEE



Radna visina:
190,0 mm



Izdubljivači:
Ø 10,0 - 55,0 mm



Dužina i širina:
238,0 x 92,0 mm



Spiralno svrdlo:
DIN 338/1897: max. Ø 16,0 mm
DIN 345: max. Ø 32,0 mm

Pribor:

- 1 Plastični transportni kofer
- 1 Imbus ključ 2.5 / 6
- 1 Sigurnosni pojas
- 1 Stezna glava Ø 1,0 - 16,0 mm
- 1 MK 3 nosač
- 1 Boca za hlađenje
- 1 Visoko učinkoviti sprej za rezanje
- 1 Upute za upotrebu



Uporaba pribora - magnetna bušilica s postoljem RU40

